

LOW VOLTAGE AC DRIVES

## ABB general purpose drives

ACS580, 125 to 150 HP 3-phase, 60 to 75 HP

1-phase, 230V



Designed to simplify drive selection, set up, operation and maintenance, the ACS580 general purpose drives conquer more applications in more industries without the head scratching complexities. The ACS580 drive is offered in a variety of options including wall-mounted, cabinet-built and packaged with disconnect means.

### One product, many applications

The drive includes all the essential components for typical light industry applications. The ACS580 is ready to control compressors, conveyors, mixers, pumps, fans, as well as many other variable and constant torque applications.

### Reliability and constant high quality

ACS580 drives are designed for customers who value high quality and robustness in their applications. Coated control boards, high enclosure classes, and motor temperature monitoring along with supervision and other protection functions ensure your processes will run smoothly – even in harsh conditions. In addition, all the drives are tested during production at maximum temperature and with nominal loads to ensure every drive performs as it should.

### Easier than ever before

ACS580 drives have all the essential features built-in, reducing commissioning and setup time. The assistant control panel with a broad set of languages is standard for ACS580 drives. You can also upgrade to an optional Bluetooth® control panel for wireless commissioning and monitoring. Primary settings and control macros ensure quick setup and the help button on the control panel offers instant advice in unclear situations.

### One part of the ACS580-01 product family

The 125 - 150 HP 230V drive is the latest addition to the ACS580-01 product family that includes drives from 1 to 350 HP at 230V, 460V, and 575V; Type 1 and 12.



## Technical data

Voltage and power range	1-phase, 230 V, +10%/-15% 3-phase, 208 to 240 V, +10%/-15% from 125 to 150 HP (3-ph); from 60 to 75 HP (1-ph)
Frequency	48 to 63 Hz
Mains choke	DC choke
Degree of protection	UL Type 1 (standard), UL Type 12 (option)
Ambient conditions	-15 to 40 °C. No frost allowed R9 from 40 to 50 °C with derating
Compliance	cULus
Control connections	Two analog inputs, two analog outputs, six digital inputs, three relay outputs, EIA-485 Modbus RTU, safe torque off (STO), USB via control panel

### Control and communication options

Fieldbus adapters	PROFIBUS DP, CANopen®, DeviceNet™, EtherNet/IP™, Modbus TCP, PROFINET IO, EtherCAT®, POWERLINK, ControlNet
Optional I/O extension modules	<b>CMOD-01:</b> External +24 V AC/DC • Two relay outputs • One digital output <b>CMOD-02:</b> External +24 V AC/DC and isolated PTC input <b>CHDI-01:</b> 115/230 V AC digital input • Six digital inputs • Two relays <b>CPTC-02:</b> ATEX-certified PTC interface and external +24 V <b>CBAI-01:</b> Bipolar I/O extension • Two bipolar analog inputs and two unipolar outputs
PC tools	Drive composer tool entry, available for free via ABB website Drive composer tool pro
Control panel options	ACS-AP-I, assistant control panel ACS-AP-W, control panel with Bluetooth interface

## Simple. Connected. All-compatible.

### Essential features inside

- Integrated safe torque off (STO)
- Removable Modbus RTU terminal
- Two option slots, one for a fieldbus adapter and one for an I/O extension
- External +24 V AC/DC (standard in R9)
- USB interface for PC tool connection
- Optimized DC choke
- Integrated EMC filter

### Get started, without the hassle

- Optional Bluetooth assistant control panel for controlling the drive up to 250 ft (75 m) and out of the arc flash boundary
- Connection to all major industrial automation systems via plug-in fieldbus and Ethernet adapters
- USB port for transferring information between PC and drive
- Optional remote monitoring module for configuring the drive parameters, and monitoring various data such as load levels, runtime, energy consumption, I/O data, and temperature of the motor bearings
- Free Drive composer software to program and monitor drive

### Learn it once, use it everywhere

- Common drives architecture enables a smooth transition to other all-compatible drives in the ABB portfolio, such as the ACS480 or ACS880
- The drives share the same user interfaces and options, enabling users to re-apply the knowledge gained with the ACS580 drives

## There is more to this drive

**A wide power range** includes drives for wall-mounting and cabinet-built drives.

**Adaptive programming** for customizing the drive for the application, without any previous programming knowledge.

**Motor control capabilities** include asynchronous motors, permanent magnet motors and synchronous reluctance motors.

Video playlist:  
ACS580 how-to  
videos



Online manuals  
for the ACS580  
drives

For more information please contact your local ABB representative or visit:

[abb.com/ACS580](http://abb.com/ACS580)  
[abb.com/drives](http://abb.com/drives)

We reserve the right to make technical changes or modify the contents of this document without prior notice. With regard to purchase orders, the agreed particulars shall prevail. ABB does not accept any responsibility whatsoever for potential errors or possible lack of information in this document.

We reserve all rights in this document and in the subject matter and illustrations contained therein. Any reproduction, disclosure to third parties or utilization of its contents – in whole or in parts – is forbidden without prior written consent of ABB. Copyright © 2019 ABB. All rights reserved.